

UPM Raflatac Technical Information

08-05-2019 EN SI

Face	SYNLITE TTR
Sales Code	BKV
Product	White, matt, PP-based film, clay-coated on one side.
Use	Thin film for product labelling and for variable information labelling in logistics and industrial chemical end-uses. Good chemical resistance.

Typical technical values

Substance	63	g/m ²	DIN 53352
Caliper	75	µm	DIN 53370
Opacity	85	%	DIN 53146/1

Printability Suitable for UV flexo, UV screen and UV Letterpress. Thermal transfer is possible with selected ribbons.

Disclaimer The performance of the product should always be tested in the actual application conditions. Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials.

All our products are sold subject to UPM Raflatac's general sales conditions, and you should ensure that any existing laws are observed.

This publication replaces all previous versions. All information is subject to change without notice.